




MECHANICAL PROTECTION

EN388:2016



4X43D

HEAT AND/OR FIRE PROTECTION

EN407:2004



X1XXXX

GDY460G

SEAMLESS KNITTED CUT-RESISTANT GLOVE WITH SMOOTH NITRILE COATING AND GRAIN LEATHER REINFORCEMENT

DESCRIPTION

- Smooth nitrile coating and grain leather palm for impermeability and grip in wet/oily environments
- Good impermeability and grip of the grain leather palm in the presence of oil residues
- Coating in liquid-proof smooth nitrile
- Advanced Knitting Technology for enhanced flexibility and comfort for the most accurate handling
- 15-gauge shell in technical yarn for excellent dexterity and tactile sensitivity
- Para-aramid stitching (double on fingertips) for extended durability
- Contact heat resistance 1 (100°C for at least 15 seconds)

FIELD OF USE

- Precision handling of very sharp and abrasive pieces, also in presence of light contact heat risk

Model	GDY460G
Environment	Wet/oily
Construction	Seamless knitted
Shell material	High tenacity elasticized HPPE/polyamide/spandex yarn reinforced with mineral fiber
Gauge	15
Coating	Liquid-proof smooth nitrile
Coating area	3/4
Reinforcement	Goat grain leather
Reinforcement area	Palm and thumb crotch
Cuff	Elasticized knitted wrist
Length (mm)	240-290
Size	7, 8, 9, 10, 11
Packing	Bag: 12 pairs / Carton: 144 pairs
Ambidextrous	No

MARKING

According to EN420 through back screen-printing
PPE Cat. II certified to EN420, EN388, EN407

Release 27/2/2019

LANZI srl Div. SAFETY SYSTEMS

Via Giulio Natta, 27/A - 10148 Torino ITALIA
Phone: +39 011 2284011 - Fax: +39 011 2284022
e-mail: sales@safety-systems.biz

REGISTRATED TRADEMARK SAFETY SYSTEMS (TO2002C002209 C.C.I.A.A. TO)

