

GIS884



SEAMLESS KNITTED CUT-RESISTANT GLOVE WITH HI-FOAM COATING

DESCRIPTION

- ▶ Soft-Shield knitting technology: maximum cut resistance with unmatched dexterity and flexibility
- ▶ HPPE inner plating for excellent comfort
- ▶ Hi-Foam coating for superior breathability and durability
- ▶ Micro-porous coating, not in contact with the user's skin, for maximum grip in dry environment
- ▶ Low-linting coating
- ▶ Anti-static according to EN16350 to prevent explosion risks in ATEX environments
- ▶ Contact heat resistance 1 (100°C for at least 15 seconds)
- ▶ Touch-screen suitable

FIELD OF USE

- ▶ Precision handling of sharp and abrasive pieces, also in presence of light contact heat risk in automotive, aerospace, mechanical, metal, glass and maintenance industry
- ▶ ATEX environments (explosive gases, vapours, mists and dusts) such as chemical and energy industry, wheat, flour or sugar silos, sawmills
- ▶ Suitable for product protection in EPA environments (ESD Protected Area) in the electrical industry and other industries involving electronical components.

MECHANICAL PROTECTION

EN388:2016



4X42F

HEAT AND/OR FIRE PROTECTION

EN407:2004



X1XXXX

OTHERS

EN16350



Release 4/11/2019

REGISTRATED TRADEMARK SAFETY SYSTEMS
(DEP.NUM. 302017000074272)



| Model | GIS884 |
|----------------|---|
| Environment | Dry or slightly wet/oily |
| Construction | Seamless knitted |
| Shell material | High tenacity elasticized HPPE/polyamide/spandex yarn with Soft-Shield technology |
| Gauge | 18 |
| Coating | Hi-Foam |
| Coating area | Palm |
| Size | 6, 7, 8, 9, 10, 11 |
| Packing | Bag: 12 pairs / Carton: 144 pairs |
| Ambidextrous | No |
| Length (mm) | 220-270 |

MARKING

According to EN420 through heat-transfer label DPI Cat. II certificato a norme EN420, EN388, EN407, EN16350

Lanzi SRL Via Giulio Natta, 27/A Torino - Italia
Phone: +39 011 2284011 - Fax: +39 011 2284022
info@lanzigroup.com